

LUPROMAX-WRC

CLEAR WIRE ROPE LUBRICANT
Environmentally friendly, non-toxic lubricant

Meeting today's lubrication needs and tomorrow's demands

LUPROMAX[®]

Lubricates • Protects • Maximizes



INTRODUCTION

LUPROMAX-WRC is a clear viscous wire rope lubricant fortified with E.P. Agents & proprietary corrosion inhibitors. The clarity of the lubricant allows ease of inspection of wire ropes. It is blended with special refined white oils, E.P. and anti-wear agents for heavy-duty work.

LUPROMAX-WRC does not contain any solvents and will not dry, harden or evaporate. It provides long term lubrication to both the core and external parts of the wire ropes. Its enhanced tackifier properties ensure good adhesion to the wire rope, providing superior performance in wet high-speed operations.

FEATURES & BENEFITS

- Enhanced Tackifier Properties
- Fast and deep penetration into the wire core
- Fortified with anti-corrosion inhibitors
- Retards the oxidation process of the chemical changes of lubricant
- Cohesive and adhesive additives
- Stabilizing agents - assures stability of the lubricant
- With E.P. & Anti-wear additives
- Ideal for wet high-speed operations.
- Water proof - totally water resistant

APPLICATIONS

- Wire Ropes Exposed to heavy mechanical stresses, e.g steel works, mining and chemical industry.
- Protection and lubrication of wire ropes of all types, e.g. on cranes and diggers, elevators, hoisting equipment.
- For wet high-speed operations.



TYPICAL PROPERTIES

APPEARANCE

- Grease

COLOUR

- Light amber

ODOUR

- Pine

FLASH POINT

- >200°C

RUST RESISTANCE(ASTM D-665)

- Pass

NLGI

- 1-2

AVAILABLE PACKAGING

- 20 litres/200 litres drum



A member of




STORAGE

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Product should not be stored above 60°C, exposed to hot sun or freezing conditions.

For more information about Lupromax products, please contact your local distributor or Magna offices:

Distributed by:



Magna

Headquarters & Far East Office: Magna International Pte Ltd

10H Enterprise Road
Singapore 629834
Tel (65) 6788-1228
Fax (65) 6785-1497
Email info@magnachem.com.sg
Website www.lupromax.com

North America Office:

1450 Government Rd West
Kirkland Lake Ontario P2N 2E9
Canada
Email magna@vappro.com
Website www.lupromax.com

Australia Office:

Unit 6, 25 Bunney Road
Oakleigh South
VIC 3167 Australia
Tel (61) 3-9558-2980
Fax (61) 3-9558-3430
Email
info@lupromax.com.au
nelsoncheng@magnaaustralia.com.au
Website www.lupromax.com.au

ISO 9001



Certificate No: AJA002706

ISO 14001



Certificate No: AJA1316783



This data sheet and the information it contains is believed to be accurate as the data of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version on this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken for any damage or injury resulting from abnormal use of material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

LUPROMAX[®]