

**FULLY SYNTHETIC
ENGINE OIL 5W-40**

HYPERION SERIES

HYPERION 7000

LUPROMAX

HAT
HEAT ACTIVATED TECHNOLOGY

A member of

STLE

Society of Tribologists
and Lubrication Engineers



A member of

NACE
INTERNATIONAL

RoHS
Compliant

RoHS COMPLIANT


EUROPEAN COMMUNITY
DIRECTIVE 2002/95/EC



LUPROMAX HYPERION 7000

NATO Stock No. 6850-32-087-9444

Fully Synthetic Engine Oil
5W-40



*Suitable for modern
high output, low
emission, super or
turbo-charged, DOHC
or GDI petrol engines*

DESCRIPTION

LUPROMAX Oil with Heat Activated Technology™ is specially developed to LUbricate, PROtect and MAXimize your engine performance.

LUPROMAX HYPERION 7000 5W-40 is a fully synthetic engine oil designed to help provide exceptional wear protection for a smooth driving experience. This technology provides maximum acceleration, torque and power for outstanding performance and reliability.

LUPROMAX HYPERION 7000 5W-40 with Heat Activated Technology™ utilizes LUPROMAX's fully synthetic technology with a high performance additive system, reducing vibration and engine noise, and enhancing shear stability for a quieter and smoother drive. Its performance has been proven in the most grueling racing applications.

LUPROMAX Oil is engineered to provide maximum power for your driving experience.

ADVANTAGES

- Help maintain engine cleanliness and continuously prevent dirt and sludge build-up
- Tested and proven to deliver improved power and acceleration
- Excellent protection at peak engine RPM and power conditions
- Excellent wear protection at high temperatures and highly effective protection from corrosion
- Helps to extend the life of engines
- Outstanding performance during the maximum oil change interval and contributes greater fuel efficiency
- Excellent flow characteristics under extreme hot and cold operating conditions and during periods of intermittent use
- Excellent anti-oxidation properties to prevent premature ageing of oil
- Reduced friction and engine noise, enhances shear stability for a quieter and smoother drive



LUPROMAX HYPERION 7000

NATO Stock No. 6850-32-087-9444

Fully Synthetic Engine Oil
5W-40

APPLICATIONS

LUPROMAX HYPERION 7000 5W-40 is designed to optimize performance and protection for modern passenger cars where API SN (and below) are recommended.

- LUPROMAX HYPERION 7000 5W-40 meets or exceeds the requirements of the industry and car manufacturer's standards required for modern high output, low emission, super or turbo-charged, DOHC or GDI petrol engines that are commonly found in the latest American, European and Japanese engine manufacturers.
- LUPROMAX HYPERION 7000 5W-40 is suitable for extreme engine stress conditions, where conventional oil often may not perform.

SPECIFICATIONS

LUPROMAX HYPERION 7000 5W-40 meets and exceeds the requirements of:

API	SN
ACEA	A3/B3, A3/B4, A5/B5, C2, C3
VW	502.00/505.00/505.01
BMW	L-04
PSA	B71 2290
MB	229.31/ 229.51
Porsche	A 40

Properties	Method	LUPROMAX HYPERION 7000
ISO Viscosity Grade	SAE J 300	5W-40
Kinematic Viscosity	@40°C cSt	ASTM D445 97.34
Kinematic Viscosity	@100°C cSt	ASTM D445 15.21
Viscosity Index	ASTM D2270	165
TBN	mgKOH/g	ASTM D2896 7.66
Flash Point	°C	ASTM D92 222
Pour Point	°C	ASTM D97 -42
Density	@15°C kg/l	ASTM D4052 0.856



HEALTH, SAFETY & ENVIRONMENT

- Health and Safety

LUPROMAX HYPERION is unlikely to present any significant health or safety hazard when used properly in the recommended application provided in the Material Safety Data Sheet (MSDS) are followed. Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained upon request through your sales contract office, or via the internet.

- Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

STORAGE

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Product should not be stored above 60°C, exposed to hot sun or freezing conditions.

AVAILABLE PACKAGING

20 liters pail/ 200 liters drum

LUPROMAX[®]

For more information about Lupromax products, please contact your local distributor or Magna offices:

Distributed by:



Headquarters & Far East Office:
Magna International Pte Ltd
10H Enterprise Road
Singapore 629834
Tel (65) 6788 1228
Fax (65) 6785 1497
Email info@magnachem.com.sg
Website <http://www.lupromax.com>

North America Office:
1450 Government Rd West
Kirkland Lake Ontario P2N 2E9
Canada
Tel 1.416 479 9151
Fax 1.888 317 1993
Email magna@vapro.com

Australia Office:
6/23-25 Bunney Rd,
Oakleigh South VIC 3167, Australia
Tel (61) 3 9558 2980
Fax (61) 3 9558 3430
Email info@lupromax.com.au
Website <http://www.lupromax.com.au>

ISO 9001



Certificate No: AJA00/2706

ISO 14001



Certificate No: AJA13/16783

This data sheet and the information it contains is believed to be accurate as the data of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version on this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken for any damage or injury resulting from abnormal use of material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.